

# **Product Data Sheet**

## **HIPRO MAG**

Hyper Viscosity Synthetic Blended Premium Gasoline Engine Oil

\_\_\_\_\_\_

## **PRODUCT FEATURES**

Hyper viscosity premium synthetic based oil, which provides extended oil drain capabilities and excellent engine wear protection.

## **APPLICATIONS**

Specially formulated for all modern high performance cars, city driving and high way cruising. Provides dependable engine protection for petrol cars including those fitted with turbo charges and/ or catalytic converters.

#### **SPECIAL PROPERTIES**

- Contains friction modifiers for better fuel economy.
- Prevents built-up of carbon deposits, maintains oil consumption control and prevents ring sticking and bore polishing.
- Good lubricating characteristic, it gives quiet operation, smooth shifting and excellent wear protection.
- Excellent engine and piston ring belt cleanliness.
- Provides maximum protection from start-up to high speed particularly during critical conditions.

#### PERFORMANCE LEVELS

API SN Plus

### TYPICAL SPECIFICATION

PROPERTY	UNIT	TEST METHOD	SAE 5W-40 SPECIFICATION
Viscosity at 40 deg C	cSt	ASTM D 445	90.65 typ
Viscosity at 100 deg C	cSt	ASTM D445	14.0 – 15.0
Viscosity Index		ASTM D 2270	150 (min) – 159 (typ)
CCS @ -30 deg C	сР	ASTM D 5293	Max 6,600
Flash Point COC	deg C	ASTM D 92	200 (min)
Pour Point	deg C	ASTM D 97	-21
Total Base Number	mgKOH/g	ASTM D 2896	7.50

<sup>\*</sup> The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. KEEP OUT OF REACH OF CHILDREN.