

Product Data Sheet

HIPRO V-TEC SAE 10W-40 API SL

HIGH PERFORMANCE LIQUID PETROLEUM GAS ENGINE OIL

PRODUCT FEATURES

V-TEC SAE 10W-40 is super high performance LPG engine oil specially formulated to provide superior engine protection for those equipped LPG tank in modern cars. It's formulated with premium quality base stocks and high TBN additives packages to provide excellent resistance to oxidation and nitration, excellent sludge and ash deposits control and superior engine cleanliness.

APPLICATIONS

Recommend for use in Japanese, European and North American vehicles operating on natural gas (NGV) CNG, or LPG and Bi-Fuel (Gas + Petrol) automotive engines.

SPECIAL PROPERTIES

- ◆ High viscosity index to facilitate low temperature starting and minimize high temperature thinning.
- ◆ Complete engine protection against wear, corrosion and rusting.
- ◆ Minimizes oil oxidation and sludge formation.
- ◆ Maintains engine cleanliness with detergent and dispersant additives.
- ◆ Prolonged engine life and maintaining engine power
- ◆ Reduces engine noise and stable to withstand high operating temperature.

PERFORMANCE LEVELS

- ◆ API SL

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

TYPICAL SPECIFICATION

			SAE 10W-40
PROPERTY	UNIT	TEST METHOD	SPECIFICATION
Density at 15 deg C	Kg/l	ASTM D4052	0.8620
Viscosity at 40 deg C	cSt	ASTM D 445	102
Viscosity at 100 deg C	cSt	ASTM D445	14.0 – 15.0
Viscosity Index		ASTM D 2270	140
CCS @ -25 deg C	cP	ASTM D 5293	Max 7,000
Flash Point COC	deg C	ASTM D 92	200 (min)
Pour Point	deg C	ASTM D 97	-21
Total Base Number	mgKOH/g	ASTM D 2896	6.70

** The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.*

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**