

## Product Data Sheet

### **HIPRO VELTORQ 0W-40**

Ultimate Performance 100% Fully Synthetic Engine Oil

---

#### **PRODUCT FEATURES**

**HIPRO VELTORQ 0W-40** is a 100% synthetic gasoline engine oil formulated with “**Salicylates Technology**” additive system combined with selected synthetic base stocks and approved viscosity modifier. Salicylates Technology improved the overall performance of engine oil and provides excellent engine cleanliness, oxidation control, strong acid neutralisation capability and long drain capability even at reduced SAPS. The 0W-40 grade delivers the viscosity required by many European car builders. It provides outstanding protection, even during extended-use driving, coupled with excellent fuel economy performance.

#### **APPLICATIONS**

Recommended for many types of modern vehicles where it will help provide unsurpassed performance even under very demanding driving conditions.

- § Latest engine technologies including turbo-charged, direct injection, diesels (without DPF) and hybrids.
- § High performance engines.
- § Most operating conditions, from mild to extreme.

*Always consult your owner's manual to check recommended viscosity grade and specifications for your vehicle.*

#### **SPECIAL PROPERTIES**

- Unsurpassed protection for high-tech multi-valve engines.
- Helps keep your engines running like new.
- Improves engines protection during the critical start-up period.
- Excellent high and low temperature performance.
- Proven low fuel consumption formula.

#### **PERFORMANCE LEVELS**

- API SN, ILSAC GF-5

---

**CAUTION:** Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

---

**TYPICAL SPECIFICATIONS**

| PROPERTY               | UNIT    | TEST METHOD | SAE 0W-40     |
|------------------------|---------|-------------|---------------|
|                        |         |             | SPECIFICATION |
| Density@15 deg C       | kg/l    | ASTM D4052  | 0.85          |
| Viscosity at 40 deg C  | cSt     | ASTM D445   | 75            |
| Viscosity at 100 deg C | cSt     | ASTM D445   | 13.0 – 15.0   |
| Viscosity Index        |         | ASTM D 2270 | 185           |
| Flash Point COC        | deg C   | ASTM D 92   | Min 230       |
| Pour Point             | deg C   | ASTM D 97   | -38           |
| Total Base Number      | mgKOH/g | ASTM D2896  | 7.30          |

\* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

**CAUTION:** Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**