

## Product Data Sheet

### **HIPRO VELTORQ 0W-20, 0W-30** **ADVANCED FUEL ECONOMY**

Advanced Fuel Economy 100% Synthetic Engine Oil

---

#### PRODUCT FEATURES

**HIPRO VELTORQ ADVANCED FUEL ECONOMY** is 100% synthetic product specially designed by selected high performance synthetic base stocks with precisely balanced components additive system. The low viscosity, advanced fully synthetic formulation helps to increase engine efficiency and improve fuel economy. Also, provides the high temperature protection of higher viscosity oils while offering the best fuel economy in the HIPRO VELTORQ Series.

#### APPLICATIONS

**HIPRO VELTORQ 0W-20** is recommended for SAE 5W-20 and 0W-20 applications in all types of gasoline fueled passenger cars, SUV's, vans, and light trucks. Recommended for extreme cold conditions to help deliver quick starts and fast lubrication.

**HIPRO VELTORQ 0W-30** is recommended for SAE 5W-30 and 0W-30 applications in all types of gasoline fueled passenger cars, SUV's, vans, and light trucks. It also recommended for extreme cold conditions to help deliver quick starts and fast lubrication. **VELTORQ 0W-30 is a "Mid SAPS" engine oils at 0.08% Phosphorus and 0.8% Sulphated Ash.**

*Always consult your owner's manual to check recommended viscosity grade and specifications for your vehicle.*

#### SPECIAL PROPERTIES

- Low viscosity, advance fully synthetic formulation help to improve fuel economy based on 0.2-2.1% potential fuel economy improvement obtained by switching from higher viscosity oils to a 0W-20 and 0W-30 grade.  
*\*Actual savings are dependent upon vehicle/engine type, outside temperature, driving conditions and your current engine oil viscosity.*
- Outstanding thermal and oxidation stability helps to reduce oil aging resulting in long lasting protection.
- Outstanding low temperature capabilities – quick cold weather starting and fast protection helps to extend engine life.

#### PERFORMANCE LEVELS

- API SN, ILSAC GF-5

---

**CAUTION:** Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

---

## TYPICAL SPECIFICATIONS

PROPERTY	UNIT	TEST METHOD	SAE 0W-20	SAE 0W-30
			SPECIFICATION	
Density@15 deg C	kg/l	ASTM D4052	0.841	0.845
Viscosity at 40 deg C	cSt	ASTM D445	45.0	58.9
Viscosity at 100 deg C	cSt	ASTM D445	7.0 – 8.5	9.3 – 10.5
Viscosity Index		ASTM D 2270	168	165
Flash Point COC	deg C	ASTM D 92	Min 220	Min 220
Pour Point	deg C	ASTM D 97	-38	-45
Total Base Number	mgKOH/g	ASTM D2896	8.30	7.30

\* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

**CAUTION:** Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**