

Product Data Sheet

HIPRO VELTORQ 504 00/507 00

Advanced Fully Synthetic Gasoline & Diesel Engine Oil

PRODUCT FEATURES

HIPRO VELTORQ 504 00/507 00 is an advanced fully synthetic formulation with the latest **“Salicylates Technology”** additive system. Salicylates Technology improved the overall performance of engine oil and provides excellent engine cleanliness, oxidation control, strong acid neutralization capability and long drain capability even at reduced SAPS. It is designed to provide superior engine responsiveness and extends the engine life with its outstanding protection against engine wear and corrosion. **HIPRO VELTORQ 504 00/507 00** specifically designed for VAG Group recent cars (VOLKSWAGEN, AUDI, SKODA, and SEAT) fitted with EURO IV and EURO V engines that require lubricants with low Sulphur, low Phosphorus and low Sulphated Ashes rates.

APPLICATIONS

HIPRO VELTORQ 504 00/507 00 recommended for all types of modern automobile engines, especially the high performance gasoline and diesel engines found in the latest passenger cars, SUVs and light vans.

HIPRO VELTORQ 504 00/507 00 is fully backward compatible over previous VW oil standards such as 501 01, 502 00, 503 00 and 503 01 for gasoline engines and 505 00, 505 01, 506 00 and 506 01 for diesel engines.

DO NOT MIX with the lubricants non VW 504 00/507 00 compliant.

Always consult your owner's manual to check recommended viscosity grade and specifications for your vehicle.

SPECIAL PROPERTIES

- Help to reduce fuel consumption, reduce wear when start-up.
- Extra cleaning performance to help prevent the formation of sludge and harmful deposits.
- Low ash, sulphur and phosphorous content.
- Outstanding thermal and oxidation stability to reduce oil aging allowing extended drain interval protection.
- Excellent overall lubrication and wear protection performance for all driving styles and conditions.
- Excellent low temperature capabilities.

PERFORMANCE LEVELS

- VW 504 00/507 00
- MB-Approval 229.51
- ACEA A3/B4-04
- BMW Longlife-04

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

TYPICAL SPECIFICATIONS

PROPERTY	UNIT	TEST METHOD	SAE 5W-30 SPECIFICATION
Density@ 15 deg C	kg/l	ASTM D4052	0.848
Viscosity at 40 deg C	cSt	ASTM D445	72
Viscosity at 100 deg C	cSt	ASTM D445	11.5
Viscosity Index		ASTM D 2270	157
Flash Point COC	deg C	ASTM D 92	Min 230
Pour Point	deg C	ASTM D 97	-42
Total Base Number	mgKOH/g	ASTM D2896	5.80

* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**