

# Product Data Sheet

## HIPRO CHAIN AND BAR OIL

SYNTHETIC BLENDED

---

### PRODUCT FEATURES

**HIPRO Chain and Bar Oil** is a blend of quality base stocks and selective additives that provides excellent performance as a chain saw bar and chain lubricant. It is specially formulated with good adhesive properties with resistance to drip and throw-off at high temperatures, and provides extreme pressure properties and rust protection in cold weather.

### APPLICATIONS

HIPRO Chain and Bar Oil is suitable for use in all makes of chain saws and all types of link chains that require lubrication, including motorcycles, and bicycles, as well as farm and industrial uses. Before changing HIPRO Chain and Bar Oil, existing deposits on the chains should be removed to ensure optimum performance of the product.

### SPECIAL PROPERTIES

- Extra stinginess for long-lasting protection.
- Extend bar, chain life
- Provide excellent friction and wear protection
- Resists dripping and throw off
- Excellent low-temperature performance.
- Reduce lubricant consumption , reduces operational cost

### TYPICAL SPECIFICATION

PROPERTY	UNIT	TEST METHOD	ISO 220
			SPECIFICATION
Viscosity at 40 deg C	cSt	ASTM D 445	210
Viscosity at 100 deg C	cSt	ASTM D445	22
Viscosity Index		ASTM D 2270	126
Flash Point COC	deg C	ASTM D 92	Min 240

\* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

---

**CAUTION:** Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

---