

Product Data Sheet

HIPRO MX3

Premium Engine Oil

PRODUCT FEATURES

MX3 Premium Engine Oil contains 100% Virgin Base Stock (High Viscosity Index) and formulated with the latest technology additives. It contains a very good lubricity agent to provide superior lubrication for all modern engines that requires multi-grade engine oil. It helps lower the maintenance cost by reducing engine wear and protecting engine running under extremely high temperature.

APPLICATIONS

Suitable for passenger cars, sport utility vehicles and light duty commercial vehicles operating on both gasoline and diesel engines.

SPECIAL PROPERTIES

- ◆ Exhibits easier cold weather starting.
- ◆ Resists breakdown at high temperature.
- ◆ Excellent fuel economy and energy efficiency.
- ◆ Oxidation stability and anti-corrosion properties.
- ◆ Maintains oil pressure and full lubrication even when hot.
- ◆ Providing a smooth engine protection including those fitted with turbo charged.

PERFORMANCE LEVELS

- ◆ API SJ/CF, JASO MA2

TYPICAL SPECIFICATION

			SAE 20W-50
PROPERTY	UNIT	TEST METHOD	SPECIFICATION
Density at 15 deg C	Kg/l	ASTM D 4052	0.8802
Viscosity at 40 deg C	cSt	ASTM D 445	150 (typ)
Viscosity at 100 deg C	cSt	ASTM D 445	17.5 – 19.5
Viscosity Index		ASTM D 2270	122
CCS @ -15 deg C	cP	ASTM D 5293	Max 9,500
Flash Point COC		ASTM D 92	220 (min)
Pour Point	deg C	ASTM D 97	-21
Total Base Number	mgKOH/g	ASTM D 2896	6.10

* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**