

Product Data Sheet

HIPRO ULTREX OUTBOARD MOTOR OIL

2-Cycle Outboard Motor Oil

PRODUCT FEATURES

Ultrex 2-Cycle Outboard Motor Oil TC-W3 is a premium quality ashless 2-cycle engine oil, designed to meet the critical requirement of all high performance, water-cooled two-cycle engines calling for TC-W3, provides maximum performance for outboard engines. It exceeds the requirement of NMMA TC-W3 standard.

APPLICATIONS

Recommended for and meets the requirement of all major outboard engine manufacturers: Yamaha, Suzuki, Tohatsu, Evinrude, Johnson, Mariner, Mercury Outboard motor. It is well suited for engines using oil injection systems with fuel/oil mixture ratios of up to 100:1.

SPECIAL PROPERTIES

- ◆ Minimizes piston rings from sticking to keep the engine operating smoothly and efficiently.
- ◆ Maximizes protection against piston and combustion chamber deposits, rust and corrosion.
- ◆ Enhance engine performance and prolong engine life.
- ◆ Eliminate gel formation due to water or other contamination.
- ◆ Extremely good aquatic toxicity properties.
- ◆ Controls engine wear even at lean fuel-to-oil mixtures.

PERFORMANCE LEVELS

- ◆ TC-W3 (Recertified Quality)

TYPICAL SPECIFICATION

PROPERTY	UNIT	TEST METHOD	Outboard Motor Oil
			SPECIFICATIONS
Density at 15 deg C	Kg/l	ASTM D4052	0.8630
Viscosity at 100 deg C	cSt	ASTM D445	6.3
Viscosity at 40 deg C	cSt	ASTM D445	34.0
Viscosity Index		ASTM D2270	138
Flash Point COC	deg C	ASTM D 92	99.0
Pour Point	deg C	ASTM D 97	-42
Colour		VISUAL	Blue

* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**