

Product Data Sheet

HIPRO PRE-DILUTED RADIATOR COOLANT

Automotive Cooling System Protector

PRODUCT FEATURES

HIPRO PRE-DILUTED RADIATOR COOLANT is a premixed or ready-to-use anti-corrosion radiator coolant which containing water-based corrosion inhibitor offering high degree of corrosion protection and prolongs the working life of water pumps and heat exchangers.

APPLICATION

Recommend for use in all cooling system in automotive engines, construction, earthmoving, mining and quarrying equipment, stationary power generation engines and marine engines.

DIRECTIONS FOR USE

1. Check cooling system for leakage
2. Drain off existing coolant and flush system
3. Fill system with HIPRO Pre-diluted Radiator Coolant.
4. Run engine for short period and check coolant level
5. Drain, flush and refill at required volume yearly

This product is harmful or fatal if ingested. If split on skin, clothes and painted surface, flush with water.

TYPICAL SPECIFICATION

PROPERTY	UNIT	TEST METHOD	SPECIFIC VALUES
Specific Gravity, 25 deg C	kg/l	ASTM D1122	1.0 – 1.12
Boiling Point	deg C	ASTM D1120	100
pH		ASTM D1287	7.5 – 11.0
Reserve Alkalinity	ml	ASTM D1121	Min 5.7
Chromates	ppm	ASTM D1687	0
Silicate	ppm		0
Amines	ppm		0
Glycols	%		0
Color			Green
Appearance			Liquid

* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**