

Product Data Sheet

HIPRO ATF D-VI

Fully Synthetic Automotive Transmission Fluid (ATF)

PRODUCT FEATURES

HIPRO ATF D-VI is a premium fully synthetic ATF that meet or exceeds the stringent requirements of GM's DEXRON-VI specification and provides excellent protection for 2006 and newer GM vehicles. It also provides improved performance in older GM vehicles, wherever DEXRON is specified.

APPLICATIONS

HIPRO ATF D-VI recommended for 2006 and newer General Motor (GM) vehicles.

SPECIAL PROPERTIES

- ◆ Improved oxidation, thermal stability, and anti-wear protection which contributes to extended transmission life.
- ◆ Excellent low temperature fluidity protects against wear under extremely cold operating conditions.
- ◆ Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration.
- ◆ Exceptional cleanliness of delicate control valves results in trouble-free transmission performance.
- ◆ Outstanding resistance against sludge and deposit formation.

PERFORMANCE LEVELS

- Meets and exceeds the requirements of General Motor's DEXRON-VI.

TYPICAL SPECIFICATION

PROPERTY	UNIT	TEST METHOD	ATF D-VI
			SPECIFICATIONS
Density at 15 deg C	Kg/l	ASTM D4052	0.8477
Viscosity at 100 deg C	cSt	ASTM D445	5.0 – 6.5
Viscosity at 40 deg C	cSt	ASTM D445	27.06
Viscosity Index		ASTM D 2270	154
Flash Point COC	deg C	ASTM D 92	224
Pour Point	mgKOH/g	ASTM D 97	-48
Colour		VISUAL	Red

* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**
