

# Product Data Sheet

## HIPRO GX 90, 140, 80W-90, 85W-140 API GL-5

Multipurpose Automotive Gear Oils

### PRODUCT FEATURES

**HIPRO GX GEAR OIL** is a multipurpose extreme-pressure gear oil meeting **API GL-5**. It is formulated from selected premium base stocks and advanced additives system to provide superior protection for heavy duty manual transmission of commercial and passenger vehicles.

### APPLICATIONS

**HIPRO GX GEAR OIL** can be used in most transmissions, rear axles, differentials and gear units of automotives and off-highway mobile equipment. It is especially suitable for hypoid and spiral-bevel gears. It can also be used in some steering gears and universal joints lubricated by oil.

### SPECIAL PROPERTIES

- ◆ Protects gear units against rust and corrosion and it function well even under shock and varying load conditions.
- ◆ Excellent thermal and oxidation stability.

### PERFORMANCE LEVELS

- ◆ API GL-5

### TYPICAL SPECIFICATION

PROPERTY	UNIT	TEST METHOD	SAE	SAE	SAE	SAE
			90	140	80W-90	85W-140
Density@15 deg C	kg/l	ASTM D4052	0.8990	0.9050	0.8850	0.9050
Viscosity at 40 deg C	cSt	ASTM D445	172	390	135	380
Viscosity at 100 deg C	cSt	ASTM D445	15 - 17	27 - 29	14 - 15	27 - 29
Viscosity Index		ASTM D 2270	95	95	95	95
Flash Point COC	deg C	ASTM D 92	Min 220	Min 220	Min 220	Min 220
Pour Point	deg C	ASTM D 97	-9	-9	-12	-12

\* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

**CAUTION:** Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**